

## IGQ LOW LEVEL RESERVE PARACHUTE (LLRP) 185 SIDE PULL

- Kicker spring and pilot chute assisted extraction for faster inflation
- Apex vent and meshed panels for superior stability
- Block constructed 20 gore Aeroconical™ canopy
- Low profile curved frame for improved visibility on landing
- Right-sided ripcord handle
- 408 lbs (185 kg) all up mass
- Fully compatible with IGQ 8M Low Level Steerable Assault Parachute (SAP), Low Level Parachute (LLP) MK1 and Carrying Straps Personal Equipment Parachutist (CSPEP) Mk3

### TECHNICAL SPECIFICATIONS

Life span	15 years (or 1 TV deployment)
All up Mass (AuM)	408 lbs (185 kg)
Rate of Descent @ 160 kg	22.6 fps (6.9 mps)
Minimum safe deployment height	250 ft (76.2 m)
Assembly weight	15.4 lbs (6.99 kg)
Height loss to full inflation	Not exceeding 98 ft (30 m)



**SAFETY IS IN THE FABRIC OF OUR BUSINESS**

IrvingQ, Llangeinor, Bridgend, United Kingdom, CF32 8PL

Tel: +44 (0) 1656 727000

Visit: [irvingq.com](http://irvingq.com)

Email: [sales@irvingq.com](mailto:sales@irvingq.com)