

IGQ 8M LOW LEVEL STEERABLE ASSAULT PARACHUTE (SAP)

Highly developed conical shape providing ultimate reliability and enhanced response:

- Designed to give total reliability in terms of inflation and height loss performance coupled with an optimised rate of descent to minimise landing injuries during low level parachuting operations
- Predictable repeatable deployment and height loss performance without post inflation collapse
- A mesh skirt to eliminate blown peripheries and resistant to line twists
- Fully compatible with the IGQ Low Level Reserve Parachute (LLRP) 185 side pull and Carrying Straps Personal Equipment Parachutist (CSPEP) Mk3

TECHNICAL SPECIFICATIONS

Life span	15 years (or 200 descents)
All up Mass (AuM)	360lbs (163 kg)
Rate of Descent @ 160 kg	17.4 fps (5.3 mps)
Minimum despatch height	328 ft (100 m)
Turn rate	12 secs for 360°
Assembly weight	33 lbs (15.1 kg)
Canopy release	Capewell quick release
Static line	Dual coloured
Harness	Adjustable

SAFETY IS IN THE FABRIC OF OUR BUSINESS

Irvin6Q, Llangeinor, Bridgend, United Kingdom, CF32 8PL

Tel: +44 (0) 1656 727000

Visit: irvingq.com

Email: sales@irvingq.com



© 2020 Irvin6Q. All Rights Reserved.